



AV 12QX



- Rugged two piece roto moulded polyethylene
- Powerful 1.7 Hp stage vacuum motor provides 115" waterlift and 95 CFM of airflow
- Features a 100 PSI diaphragm pump with bypass providing 1.1 gpm of flow
- Running at less than 60 dBA the 12 QX is excellent for both the hospitality and healthcare industries or any 24 hour facility
- The variable flow rate coupled with an adjustable vacuum shoe and brush pressure allow it to be used for both interim maintenance and restorative cleaning
- Efficient forward motion allows upwards of 2000 sq.ft./ hour to be cleaned - twice the rate of pull back self-contained units
- Other key features include, easy access removable spray bar with twist off jets and push forward design
- The spring loaded vacuum shoe ensures consistent pressure on the carpet at all times
- Pivoting vacuum shoe ensures consistent pick up even on turns while notching improves airflow for reduced drying time
- Quick release vacuum shoe and optional hard floor squeegee is available for hard floor cleaning
- Lightweight and easy to transport with the upper and lower tanks detaching into two separate units
- Accepts all optional accessories including the optional heater

MACHINE TECHNICAL SPECIFICATIONS

Chasis / Body

Body Construction:	Polyethylene
Frame:	Steel
Product Height:	39"
Product Length:	34"
Product Width:	20"
Weight -lbs.	121
Soln Tank Capacity	12
Recovery Tank Capacity	12

Vacuum and Pump

Vacuum Motor:Powerr	1250 W, 1.7 Hp
# of Stages	3
Waterlift - inches	115"
Airflow - cubic feet per minute (CFM)	95
Pump Power - Watts	100 W
Pump Pressure - PSI	100
Pump Flow - gpm	0 - 1.1
Pump Type	Bypass
Cord Length - feet	50'
Square Feet Cleaned per Hour	3000 plus
Noise Level - Decibels (dBA)	60

Cleaning and Transport System

Cleaning Width	20"
Brush Width	19"
Brush Motor Power	100 W, 0.15 Hp
Brush RPM:	1000
Brush Circuit Breaker:	

Warranty *

Body	10
Frame	5
Motors and Electrical Components	2
Labour	2

* See NaceCare warranty document for details