



## TP 18DX



- Rugged two piece roto moulded polyethylene
- Powerful 2.6 Hp ( 2 x 1.3 Hp ) 2 stage vacuum motors provides 100" waterlift and 212 CFM of airflow
- Features a 100 PSI diaphragm pump with bypass providing 1.1 gpm of flow
- Lightweight and easy to transport with the upper and lower tanks detaching into two separate units
- The large 18 gallon tanks enable it to tackle even the biggest commercial jobs
- Optional heater available

### MACHINE TECHNICAL SPECIFICATIONS

#### Chasis / Body

Body Construction:	Polyethylene
Frame:	Polyethylene
Product Height:	39"
Product Length:	37"
Product Width:	20"
Weight -lbs.	95
Soln Tank Capacity	18
Recovery Tank Capacity	18

#### Vacuum and Pump

Vacuum Motor:Power	2 - 100 W, 1.3 Hp
# of Stages	2
Waterlift - inches	100
Airflow - cubic feet per minute ( CFM )	212
Pump Power - Watts	100 W
Pump Pressure - PSI	100
Pump Flow - gpm	1.1
Pump Type	Bypass
Cord Length - feet	42'

#### Cleaning and Transport System

Cleaning Width	12"
----------------	-----

#### Warranty \*

Body	
Frame	10
Motors and Electrical Components	5
Labour	2
* See NaceCare warranty document for details	2