

DESCRIPTION

This specially-formulated epoxy ester resin sealer is designed to penetrate the surface of concrete floors. It dries to a durable, chemical-resistant finish capable of withstanding heavy usage.

WARNING: This product contains a chemical known to the State of California to cause cancer.

WARNING

Flammable liquid or vapor. Harmful if swallowed or swallowed. May cause eye and skin irritation. Keep away from heat, sparks and flame. Keep container tightly closed. Use only with adequate ventilation. Do not take internally. Avoid breathing vapor. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

FIRST AID:

IF SWALLOWED: DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Contact a physician or poison control center immediately.

IF IN EYES: Flush eyes with water for at least 15 minutes. If irritation is persistent, contact a physician.

IF ON SKIN: Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse. If irritation is persistent, contact a physician.

IF INHALED: Move person to fresh air. If irritation is persistent, contact of physician.

See M.S.D.S. for complete safety information.

KEEP OUT OF REACH OF CHILDREN

HANDLING AND STORAGE: Keep container tightly closed when not in use. Do not mix with other chemicals. Avoid excess heat and open flame. Do not store in unmarked containers. Rinse thoroughly with water before recycling container.

TOTAL SOLUTIONS™

RESILIENT FLOOR CARE

CONCRETE SEAL

Penetrates and Seals
Concrete Floors

- EPOXY ESTER RESIN
- PROTECTS FLOORS FROM THE EFFECTS OF TRAFFIC AND CHEMICALS

KEEP OUT OF REACH OF CHILDREN WARNING

Flammable liquid or vapor. Harmful if swallowed or swallowed.
May cause eye and skin irritation.
See back panel for further precautions and first aid instructions.

NET CONTENTS:

□ 5 □ 6 □ 20 □ 30 □ 35 □ 55 Gallons

Manufactured By: Total Solutions™
PO Box 240014 • Milwaukee, WI 53224

DIRECTIONS

New concrete floors must be cured a minimum of 90 days prior to sealing. Clean the floor thoroughly with detergent and water, rinse, and allow to dry for at least 2 hours. Etch the floor using 1 part concrete etcher and cleaner in 5 parts of water. This process neutralizes the alkalinity of the concrete, aiding in the penetration of the surface for better curing and adherence.

Apply this product with a lamb's wool applicator. Allow first coat to dry 4-6 hours, then apply a second coat for a smooth, slip resistant surface. Floor is traffic ready in 24 hours.

Coverage: 300-500 square feet per gallon.

This Product Contains/CAS Number: Mineral Spirits/64742-88-7; Xylene/1330-20-7; Epoxy ester Resin/Proprietary; Ethylbenzene/100-41-4; Butanoneoxime/96-29-7.

NFPA® RATINGS FLAMMABILITY

HEALTH  REACTIVITY

0124.040511