

## DESCRIPTION

This multi-purpose cleaner and degreaser contains special detergents, builders and butyl degreasers to instantly dissolve heavy dirt, grime, oil and grease deposits.

## CAUTION

Maybe harmful if swallowed. May cause eye and skin irritation. Do not take internally. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

### FIRST AID:

**IF SWALLOWED:** DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Contact a physician or poison control center immediately.

**IF IN EYES:** Flush eyes with water for at least 15 minutes. If irritation is persistent, contact a physician.

**IF ON SKIN:** Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse. If irritation is persistent, contact a physician.

**IF INHALED:** Move person to fresh air. If irritation is persistent, contact a physician. See M.S.D.S. for complete safety information.

**KEEP OUT OF REACH OF CHILDREN**

**HANDLING AND STORAGE:** Keep container tightly closed when not in use. Do not mix with other chemicals. Avoid excess heat and open flame. Do not store in unmarked containers. Rinse thoroughly with water before recycling container.

# TOTAL SOLUTIONS™

INDUSTRIAL CLEANERS  
and DEGREASERS

## SUPER SOLV #1

Concentrate Cleaner  
with 12% Butyl

- REMOVES HEAVY DIRT AND GREASE BUILD-UPS



Nonfood Compounds  
Program Listed A4  
Registration No. 135392

**KEEP OUT OF REACH OF CHILDREN**

## CAUTION

May be harmful if swallowed.  
May cause eye and skin irritation. See side panel for additional precautions and first aid instructions.

### NET CONTENTS:

□ 5 □ 6 □ 20 □ 30 □ 55 Gallons

Manufactured By: Total Solutions™  
PO Box 240014 • Milwaukee, WI 53224

## DIRECTIONS

Dilute in warm or hot water for best performance. Spray, brush or mop on and allow cleaner to penetrate and loosen deposits. Flush away with a clean water rinse.

To remove difficult or hard deposits, allow the solution to saturate the surface for 5 minutes, then rub gently with steel wool and rinse.

**USE DILUTION A FOR:** Auto, bus, truck and equipment parts, engines, transmissions and chassis, ovens, fryers and grills, kitchen hoods, and air filters.

**USE DILUTION B FOR:** Removes wax on asphalt tile, vinyl floors, terrazzo, concrete, and all other hard and resilient floors.

**USE DILUTION C FOR:** Fans and ducts, counter and hoods, motor shells, greasy parts, brick walls, skylights, and refrigerator and air conditioner coils.

**USE DILUTION D FOR:** Walls, greasy floors, gymnasiums, whitewall tires, rubber and wooden mats, floor machine pads and brushes, swimming pools, spas, and shower rooms.

**USE DILUTION E FOR:** Vinyl, rubber, linoleum tile, ceramic, and terazzo and concrete floors.

**USE DILUTION F FOR:** Lockers, files, cabinets, painted surfaces, and light cleaning on decorative surfaces.

| DILUTIONS   |             |                |
|-------------|-------------|----------------|
| APPLICATION | CONCENTRATE | PARTS OF WATER |
| A           | 1           | up to 7        |
| B           | 1           | up to 10       |
| C           | 1           | up to 12       |
| D           | 1           | up to 30       |
| E           | 1           | up to 50       |
| F           | 1           | up to 64       |

**This Product Contains/CAS Number:** Water/7732-18-5; 2-butoxyethanol/111-76-2; Alkylbenzenesulfonic acid/68584-22-5; Sodium Tripolyphosphate/7758-29-4; Sodium Metasilicate/6834-92-0.

**NFPA® RATINGS**  
FLAMMABILITY

HEALTH 2 0 REACTIVITY 0 0

0419.011011