

# Contractor



A **tough** and **robust** machine designed to enable cleaning of the highest quality to be undertaken whatever and wherever the job. The steam super-heated to 338°F nominal and delivered at 116 PSI allows the detailed cleaning of a huge variety of surfaces — from road film and gum removal to the sanitising of kitchen equipment.

The **Contractor** has a heavy duty trolley for use on rough external terrain such as pavements and concrete as well as uneven factory floors.

The chemical injection facility allows the use of a suitable mild cleaning agent. The industrial strength vacuum enables the simultaneous removal of moisture and the residue of grease and grime.

## Supplied with two comprehensive accessory kits, comprising: -

- 2 inch Round Brush (A00005)
- Triangular Brush (A00006)
- 3 x Detail Brush (Nylon) (A00020)
- 2 x Detail Brush (Wire) (A00021)
- 2 x Detail Brush (Brass) (A00022)
- Central Connector Hose & Gun (A00049) (A00196)
- Short Steam Lance (A00051)
- 2 x Single Extension Tubes (A00055)
- Multifunction Floor Tool (15.7 inches) (A00057)
- Carpet Cartridge Insert (15.7 inches) (A00059)
- Hard Floor Cartridge Insert (15.7 inches) (A00060)
- Brush Cartridge Insert (15.7 inches) (A00062)
- Multifunction Floor Tool (11.8 inches) (A00063)
- Carpet Cartridge Insert (11.8 inches) (A00065)
- 300 mm Hard Floor Cartridge Insert (A00066)
- Brush Cartridge Insert (11.8 inches) (A00068)
- Detail Nozzle (A00069)
- Detail Gulper Nozzle (A00073)
- Detail Brush (Nylon) (fits A00069) (A00020)
- 2 inch Dust Brush (A00074)
- Detail Gulper Nozzle (fits A00069) (A00075)
- Radiator Brush (A00076)
- Squeegee (A00077)
- Suction Tool (A00078)
- Brush Insert (A00079)
- Squeegee Insert (A00080)
- Small Gulper Nozzle (A00081)
- Safety Goggles (A00096)
- Safety Gloves (A00097)
- 2 x Vacuum Extension Tubes (A00101)
- Detail Nozzle (A00069)
- Floor Brush (A00106)
- Large Triangular Brush (A00107)
- Window Squeegee (A00109)

## Technical Specifications

- Electrical Supply — 230V 50/60 Hz
- Current — 3600 watts
- Water Tank — 1.32 gallon
- Chemical Tank — 2 x 1.32 gallon
- Stainless Steel Boiler — 0.8 gallon
- Steam Pressure in use — 116 PSI
- Steam Temperature — 338°F
- Heating up Time — approximately 9 minutes
- Operating Time — Continuous
- Assembled Size (L x W x H) — 36.6x 19.7 x 39.0 inch
- Weight — approximately 77 lbs
- Cable Length — 13.1 feet
- Housing Cover — Stainless steel
- Steam Adjuster — variable
- Electro Valve — For constant pressure
- Electric Cables — Silicon covered, flame proof
- Tubing — Teflon
- Safety Thermostat — Temperature limit 383°F
- Components — 2/3 nylon, 1/3 fibreglass tested to 500°F
- Electrical Switches — Water spray proofed
- Wet/Dry Vacuum — 1200 watt