



HT 1800



- Optional heater can be used on TP 8 and TP 18 SX and DX models along with AV 12 and 18 models
- Conveniently mounts to the rear of the machine
- Comes with a hi-limit thermostat for safety
- Water can pre-heated followed up by in line heating
- Temperature increase on in-line heating is directly proportional to the flow rate (gpm) so a reduction in water flow will augment a greater increase in temperature (see specs for details)

MACHINE TECHNICAL SPECIFICATIONS

Chassis / Body

Body Construction:	Steel
Voltage	120 V, 50 / 60 Hz
Product Height:	13.3"
Product Length:	4.3"
Product Width:	6.3"
Weight -lbs.	14
Power Cord	50'

Heating Specifications

Pre- Heating == 15 Degree F Increase

8 gallon Unit	7 minutes
12 gallon Unit	10 minutes
18 gallon Unit	15 minutes

In- Line Heating - Temperature Increase

Hand Tool - 114 degree F	50 % Flow
Hand Tool - 76 degree F	75 % Flow
Hand Tool - 57 degree F	100 % Flow
Floor Tool, 3 Jet Wand - 100 degree F	50 % Flow
Floor Tool, 3 Jet Wand - 66 degree F	75 % Flow
Floor Tool, 3 Jet Wand - 50 degree F	100 % Flow