



8 Minutes- 2 Minutes to Foam and 6 mins to rinse and complete

Water Consumption - gallons

RM 800F

- · Rugged two piece roto moulded polyethylene
- Powerful 1.3 Hp 2 stage vacuum motor provides 90" waterlift and 95 CFM of airflow
- Features a 135 PSI diaphragm pump providing 1.0 gpm of flow
- Foam is applied at low pressure through the gun by mixing water and chemical with compressed air
- Powerful onboard compressor creates 114 PSI of air pressure to create thick foam.
- Powerful blower with a 4 1 stretch hose which expands to over 30 feet for drying surfaces
- Extensive hose wrap system for solution hose, vac hose and blower hose allows everything to be stored onboard without clutter
- All the tools required for the job including the chemical are stored onboard
- DEMA metering tip controlled chemical feed system ensuring correct dilution
- Large drain hose preventing clogging when draining
- · Unit comes complete with a laminated user guide
- The large 8 gallon tanks enable it to tackle even the largest restrooms
- Lightweight and easy to transport with the upper and lower tanks detaching into two separate units
- User benefits include labour savings, improved cleaning results versus manual systems, along with reduced water consumption

MACHINE TECHNICAL SPECIFICATIONS			
Chassis / Body		Vacuum and Pump	
Body Construction:	Polyethylene	Vacuum Motor:Power	1000 W, 1.3 Hp
Frame:	Steel	# of Stages	2
Product Height:		Waterlift - inches	100
Product Length:		Airflow - cubic feet per minute (CFM)	106
Product Width:		Compressor	350 W, 1/2 hp
Weight	130	Pump Pressure Operating - PSI	135
Sol'n Tank Capacity	8	Pump Flow - gallon per minute	1 gpm
Recovery Tank Capacity	8	Chemical Dilution	Automatic
Hose System		Warranty *	
Vac Hose	33'	Body	10
Blower Hose (Extendable)	33'	Frame	5
Solution Hose	33'	Motors and Electrical Components	2
Cord Length - feet	33'	Labour	2
		* See NaceCare warranty document for details	
Performance on 240 sq. ft of Wall - 6 Fixtures			