



TP 18DX



- Rugged two piece roto moulded polyethylene
- Powerful 2.6 Hp (2 x 1.3 Hp) 2 stage vacuum motors provides 100" waterlift and 212 CFM of airflow
- Features a 100 PSI diaphragm pump with bypass providing 1.1 gpm of flow
- Lightweight and easy to transport with the upper and lower tanks detaching into two separate units
- The large 18 gallon tanks enable it to tackle even the biggest commercial jobs
- Optional heater available

MACHINE TECHNICAL SPECIFICATIONS

Chasis / Body

| | |
|------------------------|--------------|
| Body Construction: | Polyethylene |
| Frame: | Polyethylene |
| Product Height: | 39" |
| Product Length: | 37" |
| Product Width: | 20" |
| Weight -lbs. | 95 |
| Soln Tank Capacity | 18 |
| Recovery Tank Capacity | 18 |

Vacuum and Pump

| | |
|---|-------------------|
| Vacuum Motor:Power | 2 - 100 W, 1.3 Hp |
| # of Stages | 2 |
| Waterlift - inches | 100 |
| Airflow - cubic feet per minute (CFM) | 212 |
| Pump Power - Watts | 100 W |
| Pump Pressure - PSI | 100 |
| Pump Flow - gpm | 1.1 |
| Pump Type | Bypass |
| Cord Length - feet | 42' |

Cleaning and Transport System

| | |
|----------------|-----|
| Cleaning Width | 12" |
|----------------|-----|

Warranty *

| | |
|--|----|
| Body | |
| Frame | 10 |
| Motors and Electrical Components | 5 |
| Labour | 2 |
| * See NaceCare warranty document for details | 2 |