



TP 18SX



- Rugged two piece roto moulded polyethylene
- Powerful 1.7 Hp stage vacuum motor provides 115" waterlift and 95 CFM of airflow
- Features a 100 PSI diaphragm pump with bypass providing 1.1 gpm of flow
- Lightweight and easy to transport with the upper and lower tanks detaching into two separate units
- The large 18 gallon tanks enable it to tackle even the biggest commercial jobs
- Optional heater available

MACHINE TECHNICAL SPECIFICATIONS

Chasis / Body

Body Construction:	Polyethylene
Frame:	Polyethylene
Product Height:	39"
Product Length:	37"
Product Width:	20"
Weight -lbs.	92
Soln Tank Capacity	18
Recovery Tank Capacity	18

Vacuum and Pump

Vacuum Motor:Power	1250 W, 1.7 Hp
# of Stages	3
Waterlift - inches	115"
Airflow - cubic feet per minute (CFM)	95
Pump Power - Watts	100 W
Pump Pressure - PSI	100
Pump Flow - gpm	1.1
Pump Type	Bypass
Cord Length - feet	42

Cleaning and Transport System

Cleaning Width	12"
----------------	-----

Warranty *

Body	
Frame	10
Motors and Electrical Components	5
Labour	2
* See NaceCare warranty document for details	2