

WV 1800P



- Powerful 1.6 Hp vacuum motor with 2 year warranty providing excellent water recovery
- Motor provides 110" waterlift and 95 CFM of airflow
- Ball float wet shut-off assembly ensures water does not reach the motor and vapour barriers can be added to eliminate moisture completely
- Structural foam tank comes complete with a 10 year warranty
- Structofoam head material is rustproof and durable with a 10-year warranty against defects
- Float activated sump pump allows continuous pumping of fluid without interrupting the vacuuming process
- Ideal for floods, water pipe ruptures, drain back-ups and industrial spills
- Pumps water at a rate of 60 gallons per minute
- The submersible pump is made of durable, high-impact plastics for heat and chemical resistance
- The motor uses a stainless steel shaft and triple seal system and has a thermal protection device to prevent overheating

Machine Technical Specifications			
Chasis/Body Construction		<u>Specifications</u>	
Head	Structural Foam	Vacuum Motor: - Watts	1,200 Watt
Tank	Structural Foam	Horsepower:	1.6 Hp
		Vacuum Motor-Stages - 2 speed	2 Stage
<u>Dimensions</u>		Airflow	95 cfm
Product Height:	37"	Waterlift at Sealed Orifice:	100"
Product Length:	31"	Noise Level - Decibels (dBA)	64 dBA
Product Width:	27"	Cord Length	42'
Product Weight:	81 lbs.		
Tank Capacity	20 gal.	Warranty *	
		Body	10 Years
Pump Assembly		Frame	Not Applicable
Pump Power	500 Watt, 0.75 Hp	Motors and Electrical Components	2 Years
Pump Type - Float activated	Centrifugal	Labour	2 Years
Pump Output	60 gpm	* See NaceCare warranty document for details	
Vertical Lift	7 gpm @ 22 Feet		
Heat and Chemical resistant	100 degrees F		
Stainless steel shaft			
Thermally protected			