Automatic Scrubbers

CT 40



10/13 Gallon, 20" - Brush and Traction Drive

High Productivity



Large solution capacity in a minimum external space



Extensive running time, large battery compartment



Solution Control with automatic stop



Available in brush or traction drive



Brush Control with delayed automatic stop









Automatic Scrubbers







High Performance



CFS (Center Flow System) Solution distribution from brush center



CWS (Constant Weight System) Ensures maximum scrubbing results



Exclusive squeegee system assures high performance at low cost



High quality / high performance vacuum

Ergonomics, User Friendly



Great maneuverability due to optimum weight distribution



Great working visibility



Designed to assure Minimum noise levels



Easy to use control panel



Battery level indicator



Recovery tank discharge hose at maximum height



Recovery tank can be tilted for ease of cleaning



On board charger can be easily installed now or later



External battery charger plug

Low Maintenance Costs



Inlet and outlet filters for maximum solution tank protection



AFS (Anti Foam System) and shut off sensor protect vacuum



Spin-on spin-off brush/pad driver (single brush only)



Squeegee blade can be used on 4 sides before replacement



Squeegee assembly and blade replacement without tools



Easy access to internal compartments





Automatic Scrubbers CT 40







Durability



Tanks and surrounding body in high density polyethylene



Oil bath reduction gear box



Brush head designed to absorb harsh impact



Squeegee system designed to absorb harsh impact



Panel control switches protected against water and humidity







Technical data		B 50	BT 50
Drive System		Brush	Traction
Scrubbing width	Inches/mm.	20"/500 mm	20"/500 mm
Squeegee width	Inches/mm.	32"/815mm	32"/815mm
No. of brushes		1 (disc)	1 (disc)
Solution tank capacity	Gal/Ltr	10 Gal/40 Ltr	10 Gal/40 Ltr
Recovery tank capacity	Gal/Ltr	13 Gal/50 ltr	13 Gal/50 ltr
Battery power supply	Volts	24V	24V
	Amp Hours	105/145 Ah	105/145 Ah
Empty weight without batt.	Lbs/kg	183 lbs/83 Kg	183 lbs/83 Kg
Length	Inches/mm.	48 "/1230mm	48 "/1230mm
Width	Inches/mm.	20.5"/516mm	20.5"/516mm
Height	Inches/mm.	38"/962 mm	38"/962 mm
Electro-valve solution flow		Yes	Yes
Electric traction			Yes
Max speed	mph/Kmh	2.2 mpg/3.5 kgh	2.8 mph/4.5 Kgh

Automatic Scrubbers **CT 40**





Competitive Advantages



Exclusive squeegee system assures high performance

Incomparable drying results even on the most difficult surfaces due to a very unique design.



Maximum protection for the vacuum motor (water level sensor)

1. The vacuum motor is mounted in the highest part of the machine and is protected by a filter and water level sensor.

2. When the dirty water tank is full, the left LED lights up and the vacuum motor shuts down. The right LED indicates when the cleaning solution has reached the reserve and there is enough solution for about two minutes.



Large tank capacity in minimum external space

10/13 gallon (40-45 liter) capacity makes this model very unique in its category.



Brush control with automatic delayed stop

Saves brush wear and protects the floor surface. Brush rotation stops (3 sec. delay on traction drive) and starts upon brush activation.



Solution control with automatic stop

Saves water and chemicals. Solution flow stops and starts upon brush activation.



Recovery tank can be tilted

Easy to rinse and clean with smooth internal finishes.



IPC Eagle Corporation Sales and Service Provided by: